


Type Designation	4122
Designation IEC	6LP3146
System	Zn-MnO ₂ (Alkaline)
Shelf Life (Coding)*	5 years
Nominal Voltage [V]	9
Typical Capacity C [mAh]	565 (discharge with high-resistance)
Permissible Temperature Range	- 10 °C ... 50 °C
Weight, approx. [g]	46
Volume [ccm]	20.8



Dimensions [mm]	min:	max:
A	46.5	48.5
D	-	46.4
E	12.45	12.95
O	24.5	26.5
P	15.5	17.5



Typical Capacities (at 20°C):

Discharge Type	Load	End Voltage[V]	7.5
24H/D, 7D/H – 1S/1H, 24H/1D	10000Ω -	Time [h]	470
	620Ω	Capacity [mAh]	394
		Energy [mWh]	3289
Smoke Detector			
Discharge Type	Load	End Voltage[V]	5.4
1H/D, 7D/W	270 Ω	Time [h]	20,9
		Capacity [mAh]	560
		Energy [mWh]	4154
Toy			
Discharge Type	Load	End Voltage[V]	5.4
2H/D, 7D/W	620 Ω	Time [h]	48,7
		Capacity [mAh]	565
		Energy [mWh]	4257
Radio			

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries

* In consideration of typical loss of capacity at storage and application.