



Designation IEC:	HR 6
Size:.....	AA
Nominal Voltage:.....	1.2 V
Rated Capacity:.....	2600 mAh
Internal Resistance DC; fully charged:.....	48 mΩ
Impedance AC at 1 kHz; fully charged:.....	35 mΩ
Max. Discharge Current (continuous load / 0.8 V):.....	5.2 A

Typical Capacity at:	
0.2 C / 1.0 V:.....	2600 mAh
1.0 C / 0.9 V:.....	2400 mAh

Charge Retention:
65 % of initial capacity after one year storage at 20 °C; determined at 0.2 C discharge rate

Dimensions:	
Diameter a:.....	14.5^{-1.0} mm
Height b:.....	50.5^{-1.3} mm
Shoulder Height c:.....	49.5^{-1.3} mm
Cap Diameter d:.....	5.5^{-1.3} mm
Volume:.....	8 cm³
Weight (approx.):.....	32 g

Charge Conditions at:	
Standard Charge:.....	260 mA, 16 h
Fast Charge:.....	2600 mA (-dV)
Trickle Charge (0.03 - 0.05 C):.....	78 - 130 mA

Temperatures (recommended / permissible) at:	
Storage:.....	-20 °C ... 25 °C / -20 °C ... 40 °C
Charge:.....	15 °C ... 30 °C / 0 °C ... 45 °C
Fast Charge:.....	15 °C ... 30 °C / 0 °C ... 40 °C
Discharge:.....	0 °C ... 40 °C / 0 °C ... 50 °C

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries