	<b>MATERIAL SAFETY DATA SHEET</b>	Page : 1 of 8
		Revised edition no : 7
		Date : 9 / 11 / 2011
		Supersedes : 31 / 10 / 2010
<b>ARGON</b>		<b>003A</b>



2.2 : Non flammable, non toxic gas.

**Warning**



## SECTION 1. Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name : ARGON  
 SDS Nr : 003A  
 Chemical description : Argon  
 CAS No :007440-37-1  
 EC No :231-147-0  
 Index No :---  
 Registration-No. : Listed in Annex IV / V REACH, exempted from registration.  
 Chemical formula : Ar

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional. Perform risk assessment prior to use.  
 Test gas / Calibration gas. Purging. Laboratory use.  
 Contact supplier for more uses information

### 1.3. Details of the supplier of the safety data sheet

Company identification : Sapio Produzione Idrogeno Ossigeno Srl  
 Via S. Pellico, 48  
 20900 Monza ITALIA  
 E-Mail address (competent person) : sds@sapio.it

### 1.4. Emergency telephone number

Emergency telephone number : +39 0295705444

## SECTION 2. Hazards identification

### 2.1. Classification of the substance or mixture

#### Hazard Class and Category Code Regulation EC 1272/2008 (CLP)


• Physical hazards : Gases under pressure - Compressed gas - Warning - (CLP : Press. Gas) - H280

#### Classification EC 67/548 or EC 1999/45

: Not classified as dangerous substance/mixture.  
 Not included in Annex VI.  
 No EC labelling required.

### 2.2. Label elements

#### Labelling Regulation EC 1272/2008 (CLP)

	<b>MATERIAL SAFETY DATA SHEET</b>	Page : 2 of 8
		Revised edition no : 7
		Date : 9 / 11 / 2011
		Supersedes : 31 / 10 / 2010
<b>ARGON</b>		<b>003A</b>

## SECTION 2. Hazards identification (continued)

### • Hazard pictograms



- Hazard pictograms code : GHS04
- Signal word : Warning
- Hazard statements : H280 - Contains gas under pressure; may explode if heated.
- Precautionary statements : P403 - Store in a well-ventilated place.
- Storage

### Labelling EC 67/548 or EC 1999/45

: No EC labelling required.

### 2.3. Other hazards

: Asphyxiant in high concentrations.

## SECTION 3. Composition/information on ingredients

### 3.1. Substance / 3.2. Mixture

Substance.

Substance name	Contents	CAS No	EC No	Index No	Registration no	Classification
Argon	: 100 %	7440-37-1	231-147-0	-----	* 1	Not classified (DSD/DPD) Press. Gas (H281)

Contains no other components or impurities which will influence the classification of the product.

\* 1: Listed in Annex IV / V REACH, exempted from registration.

\* 2: Registration deadline not expired.

\* 3: Registration not required: Substance manufactured or imported < 1t/y

Full text of R-phrases see chapter 16. Full text of H-statements see chapter 16

## SECTION 4. First aid measures

### 4.1. Description of first aid measures


- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
- Skin contact : Adverse effects not expected from this product.
- Eye contact : Adverse effects not expected from this product.
- Ingestion : Ingestion is not considered a potential route of exposure.

### 4.2. Most important symptoms and effects, both acute and delayed

: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/ consciousness. Victim may not be aware of asphyxiation.

### 4.3. Indication of any immediate medical attention and special treatment needed

: None.

	MATERIAL SAFETY DATA SHEET	Page : 3 of 8
		Revised edition no : 7
		Date : 9 / 11 / 2011
		Supersedes : 31 / 10 / 2010
ARGON		003A

## SECTION 5. Fire-fighting measures

### 5.1. Extinguishing media

#### Extinguishing media

- Suitable extinguishing media : All known extinguishants can be used.

### 5.2. Special hazards arising from the substance or mixture

- Specific hazards : Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products : None.

### 5.3. Advice for fire-fighters

- Specific methods : If possible, stop flow of product.  
Coordinate fire measure to the surrounding fire. Cool endangered containers with water spray jet from a protected position. Do not empty contaminated fire water into drains.
- Special protective equipment for fire fighters : In confined space use self-contained breathing apparatus.

## SECTION 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- : Try to stop release.  
Evacuate area.  
Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.  
Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.  
Ensure adequate air ventilation.

### 6.2. Environmental precautions

- : Try to stop release.

### 6.3. Methods and material for containment and cleaning up

- : Ventilate area.

### 6.4. Reference to other sections

- : See also sections 8 and 13.

## SECTION 7. Handling and storage


### 7.1. Precautions for safe handling

#### Safe use of the product

- : Only experienced and properly instructed persons should handle gases under pressure. The product must be handled in accordance with good industrial hygiene and safety procedures.  
Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.  
Do not smoke while handling product.  
Ensure the complete gas system was (or is regularly) checked for leaks before use.

#### Safe handling of the gas receptacle

- : Refer to supplier's container handling instructions.  
Suck back of water into the container must be prevented.  
Do not allow backfeed into the container.  
Protect cylinders from physical damage; do not drag, roll, slide or drop.  
When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.  
Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.  
If user experiences any difficulty operating cylinder valve discontinue use and contact supplier.  
Never attempt to repair or modify container valves or safety relief devices.  
Damaged valves should be reported immediately to the supplier.  
Keep container valve outlets clean and free from contaminates particularly oil and water.

	MATERIAL SAFETY DATA SHEET	Page : 4 of 8
		Revised edition no : 7
		Date : 9 / 11 / 2011
		Supersedes : 31 / 10 / 2010
ARGON		003A

## SECTION 7. Handling and storage (continued)

Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.  
 Close container valve after each use and when empty, even if still connected to equipment.  
 Never attempt to transfer gases from one cylinder/container to another.  
 Never use direct flame or electrical heating devices to raise the pressure of a container.  
 Do not remove or deface or modify labels provided by the supplier for the identification of the cylinder contents.

### 7.2. Conditions for safe storage, including any incompatibilities

: Keep container below 50°C in a well ventilated place.  
 Observe all regulations and local requirements regarding storage of containers. Containers should be stored in the vertical position and properly secured to prevent toppling. Stored containers should be periodically checked for general condition and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible materials.  
 Containers should not be stored in conditions likely to encourage corrosion.

### 7.3. Specific end use(s)

: None.

## SECTION 8. Exposure controls/personal protection

### 8.1. Control parameters

DNEL: Derived no effect level : None available.  
 PNEC: Predicted no effect concentration : None available.

### 8.2. Exposure controls

Appropriate engineering controls : Oxygen detectors should be used when asphyxiating gases may be released.  
 Consider work permit system e.g. for maintenance activities.  
 Systems under pressure should be regularly checked for leakages.  
 Provide adequate general and local exhaust ventilation.

Individual protection measures, e.g. personal protective equipment : A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk.  
 The following recommendations should be considered.  
 Wear leather safety gloves and safety shoes when handling cylinders.  
 Wear safety glasses with side shields

Environmental exposure controls : None necessary.

## SECTION 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance

- Physical state at 20°C / 101.3kPa : Gas.

- Colour : Colourless.

Odour : No odour warning properties.

Odour threshold : Odour threshold is subjective and inadequate to warn for overexposure.

Melting point [°C] : -189


Boiling point [°C] : -186

Flash point [°C] : Not applicable for gases and gas-mixtures.

Evaporation rate (ether=1) : Not applicable for gases and gas-mixtures.

Flammability range [vol% in air] : Non flammable.

Vapour pressure [20°C] : Not applicable.

	MATERIAL SAFETY DATA SHEET	Page : 5 of 8
		Revised edition no : 7
		Date : 9 / 11 / 2011
		Supersedes : 31 / 10 / 2010
ARGON		003A

## SECTION 9. Physical and chemical properties (continued)

Relative density, gas (air=1)	: 1.38
Relative density, liquid (water=1)	: Not applicable.
Solubility in water [mg/l]	: 61
Partition coefficient n-octanol/water	: Not applicable for inorganic gases.
Auto-ignition temperature [°C]	: Not applicable.

### 9.2. Other information

Other data	: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.
Molar mass [g/mol]	: 40
Critical temperature [°C]	: -122

## SECTION 10. Stability and reactivity

### 10.1. Reactivity

: No reactivity hazard other than the effects described in sub-sections below.

### 10.2. Chemical stability

: Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

: None.

### 10.4. Conditions to avoid

: None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

: None.  
For additional information on compatibility refer to ISO 11114


### 10.6. Hazardous decomposition products

: None.

## SECTION 11. Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity	: No known toxicological effects from this product.
Skin corrosion/irritation	: No known effects from this product.
Serious eye damage/irritation	: No known effects from this product.
Respiratory or skin sensitisation	: No known effects from this product.
Reproductive toxicity	: No known effects from this product.
STOT-single exposure	: No known effects from this product.
STOT-repeated exposure	: No known effects from this product.
Aspiration hazard	: Not applicable for gases and gas-mixtures.

	MATERIAL SAFETY DATA SHEET	Page : 6 of 8
		Revised edition no : 7
		Date : 9 / 11 / 2011
		Supersedes : 31 / 10 / 2010
ARGON		003A

## SECTION 12. Ecological information

### 12.1. Toxicity

: No known ecological damage caused by this product.

### 12.2. Persistence - degradability

: No data available.

### 12.3. Bioaccumulative potential

: No data available.

### 12.4. Mobility in soil

: No data available.

### 12.5. Results of PBT and vPvB assessment

: Not classified as PBT or vPvB.

### 12.6. Other adverse effects

Effect on ozone layer : None.

Effect on the global warming : None.

## SECTION 13. Disposal considerations

### 13.1. Waste treatment methods

: Do not discharge into any place where its accumulation could be dangerous.  
May be vented to atmosphere in a well ventilated place.

### 13.2. Additional information

: None.

## SECTION 14. Transport information

UN number : 1006

Labelling ADR, IMDG, IATA



: 2.2 : Non flammable, non toxic gas.

### Land transport (ADR/RID)

H.I. nr : 20

UN proper shipping name : ARGON, COMPRESSED

Transport hazard class(es) : 2

Classification code : 1 A

Packing Instruction(s) : P200

Tunnel Restriction : E : Passage forbidden through tunnels of category E.

Environmental hazards : None.


### Sea transport (IMDG)

Proper shipping name : ARGON, COMPRESSED

Class : 2.2

Emergency Schedule (EmS) - Fire : F-C

Emergency Schedule (EmS) - Spillage : S-V

	MATERIAL SAFETY DATA SHEET	Page : 7 of 8
		Revised edition no : 7
		Date : 9 / 11 / 2011
		Supersedes : 31 / 10 / 2010
ARGON		003A

#### SECTION 14. Transport information (continued)

Packing instruction	: P200
<b>Air transport (ICAO-TI / IATA-DGR)</b>	
Proper shipping name (IATA)	: ARGON, COMPRESSED
Class	: 2.2
Passenger and Cargo Aircraft	: Allowed.
Packing instruction - Passenger and Cargo Aircraft	: 200
Cargo Aircraft only	: Allowed.
Packing instruction - Cargo Aircraft only	: 200

#### Special precautions for user

- : Avoid transport on vehicles where the load space is not separated from the driver's compartment.
- Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.
- Before transporting product containers :
  - Ensure that containers are firmly secured.
  - Ensure cylinder valve is closed and not leaking.
  - Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
  - Ensure valve protection device (where provided) is correctly fitted.
  - Ensure there is adequate ventilation.

#### SECTION 15. Regulatory information

##### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

###### EU legislation

Restrictions on use	: None.
Seveso directive 96/82/EC	: Not covered.
	: Ensure all national/local regulations are observed.

##### 15.2. Chemical Safety Assessment


- : A CSA does not need to be carried out for this product.

#### SECTION 16. Other information

Indication of changes	: Revised safety data sheet in accordance with commission regulation (EU) No 453/2010
Training advice	: The hazard of asphyxiation is often overlooked and must be stressed during operator training.
List of full text of H-statements in section 3.	: H281 - Contains refrigerated gas; may cause cryogenic burns or injury.
Note	: This Safety Data Sheet has been established in accordance with the applicable European Union legislation.
DISCLAIMER OF LIABILITY	: Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted. Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

This document has been prepared in accordance with the MSDS requirements of the national codes of practice declared by NOHCS under s.38(1) of the National Occupational Health and Safety Commission Act 1985 (Cwlth).

**DISCLAIMER OF LIABILITY** The information in this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this

	MATERIAL SAFETY DATA SHEET	Page : 8 of 8
		Revised edition no : 7
		Date : 9 / 11 / 2011
		Supersedes : 31 / 10 / 2010
ARGON		003A

product. If the product is used as a component in another product, this MSDS information may not be applicable.

**End of document**